


<div>Year:<b>2023</b></div> <div>Make:<b>Chevrolet</b></div> <div>Model:<b>Silverado Chassis Cab</b></div> <div>VIN:<b>1HTKHPVK1PH284466</b></div>	<div>Engine:<b>Engine, Duramax 6.6L Turbo-Diesel V8</b></div> <div>Transmission:<b>Automatic</b></div> <div>Colors:<b>Summit White/Jet Black Cloth Seat Trim</b></div>
<div><div>CITY MPG /HIGHWAY MPG</div><div>NA</div><div><small>*MPG estimates on this website are EPA estimates; your actual mileage may vary. For used vehicles, MPG estimates are EPA estimates for the vehicle when it was new. The EPA periodically modifies its MPG calculation methodology; all MPG estimates are based on the methodology in effect when the vehicles were new (please see the Fuel Economy portion of the EPA's website for details, including a MPG recalculation tool).</small></div></div> <div></div>	<div>Price:<b>\$64,939</b></div> <div><small>*Prices do not include additional fees and costs of closing, including government fees and taxes, any finance charges, any dealer documentation fees, any emissions testing fees or other fees. All prices, specifications and availability subject to change without notice. Contact dealer for most current information</small></div>

Entertainment

- 6-speaker audio system

-SiriusXM, delete
- Audio system, 4.2" diagonal color display AM/FM stereo with USB port and auxiliary jack (Requires (AE7) front 40/20/40 split-bench seat. Not available with (UE1) OnStar or (U2K) SiriusXM Radio.)

Exterior

- Antenna, fixed mast

-Bumper, front, Black

-Front fender extension, painted body color

-Grille guard screen, insect protection (mounted behind grille)

-Headlamps, halogen projector-beam

-Lamps, cargo area, cab mounted with switch on center switch bank

-Mirrors, outside high-visibility vertical camper-style, Black with manual folding and extension and lower convex spotter glass

-Tires, front 225/70R19.5G highway blackwall Pirelli Max Axle Load: 7,940 lb. (Standard on models built after July 17th, 2023) (Requires (YEE) Tires, rear 225/70R19.5G highway blackwall Pirelli, Max Axle Load: 15,000 lb. or (YEZ) Tires, rear 225/70R19.5G traction blackwall Pirelli, Max Axle Load: 15,000 lb.)

-Wheel, spare delete
- Assist steps

-Door handles, Black

-Glass, solar absorbing, tinted

-Grille, base, molded in color, Black

-Lamps, Smoked Amber roof marker

-Lamps, rear, stop/turn/backup (1-piece assembly) with license plate light

-Spare tire delete

-Tires, rear 225/70R19.5G highway blackwall Pirelli Max Axle Load: 15,000 lb. (Standard on models built after July 17th, 2023) (Requires (XEY) Tires front 225/70R19.5G Highway blackwall Pirelli.)

-Wheels, 19.5" x 6.75", steel, Black painted, 8-holes, hub piloted

Interior

- Air conditioning, single-zone

-Cruise control, steering wheel-mounted

-Driver Information Center, 3.5-inch diagonal monochromatic display, provides warning messages and basic vehicle information

-Instrumentation, 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure

-Mirror, inside rearview manual day/night

-Seat trim, Vinyl

-Seats, front 40/20/40 split-bench, 3-passenger driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar.

-Steering column, manual Tilt-Wheel

-Upfitter switch kit provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel

-Windows, power with driver express up and down and express down on all other windows
- Assist handle, front passenger and driver on A-pillars

-Door locks, power

-Floor covering, Graphite-colored rubberized-vinyl

-Interior trim, Jet Black/Dark Ash (Required and only available with (H2Q/H2R) Dark Ash seats with Jet Black interior accents.)

-Seat Belt, Black

-Seat, rear 60/40 folding bench (folds up), 3-passenger (includes child seat top tether anchor)

-Speedometer, miles/kilometers

-Steering wheel, urethane

-Visors, driver and front passenger, vinyl

Mechanical

- Alternator, 150 amps

-Axle to End of Frame, 49" (Requires wheelbase (EM1) 199" or (FNV) 175". Not available with (G40), (GP1) or (GP8) rear air suspension.)

-Batteries, heavy-duty dual 1100 cold-cranking amps includes battery box mounted to left side under cab

-Capped Fuel Fill

-Engine, Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2700 rpm, 700 lb.-ft. torque @ 1600 rpm

-Exhaust system, rear exit

-Front suspension, 7,000 lb. (3,175 kg) multi-leaf, includes shock absorbers

-Fuel, diesel B20

-Highway Service Transmission, Automatic close-ratio 6 SPD with double overdrive, Allison, A1700HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR, (C7R) 16,500 lb. GVWR, (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).)

-Neutral-at-Stop Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop, and remains in neutral until the service brake is released

-Rear axle, 4.10 ratio Max road speed: 79 MPH

-Rear wheel drive

-Trailer brake controller, integrated

-Transmission shift control calibration, fuel sense Performance
- Axle lubricant, rear, synthetic oil EmGard FE -75W-90

-Axle, Open rear axle, non-locking rear

-Brakes, hydraulic, heavy duty Bosch/Meritor/Wabco system with 4-channel (ABS) (Includes (J69) driveline park brake.)

-Emissions, USA 50 State certified

-Exhaust brake

-Front axle, 7,000 lb., Dana Spicer D800-N, "I"-beam, non-driving (Requires (FK6) 7,000 lb. (3,175 kg) front suspension.)

-Fuel tank, rear only, 40 gallon mounted between frame side rails and behind rear axle

-GVWR, 16,500 lb. (7484 kg) (Silverado 4500 HD 2WD Crew Cab models require one of the following combinations: (1) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension or (G40) 12K Rear air suspension. (2) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension, (FUT) 15.5k rear suspension, (GP1) 13.5K rear air suspension, (GP8) 15.5k rear air suspension, (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.)

-Incomplete vehicle

-Rear axle, 10,000 lb. (4,536 kg) Dana Spicer S14-110, single reduction

-Rear suspension, 11,000 lb. (4,990 kg) multi-leaf, vari-rate (Not available with air suspension.)

-Steering, power (Bosch S2 8014 Plus)

-Trailer provisions, trailering wire harness only, trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.

-Wheelbase, 175" (444.5 cm), 60" CA (Requires (F0C) 49" axle to end of frame. Not available with (G40) 12,000 lb., (GP1) 13,500 lb. or (GP8) 15,500 lb. rear air suspension, or (NPK) Exhaust System.)

Safety

- Airbag deactivation switch, frontal passenger-side (Included and only available with (AY0) airbags.)
- Brake, parking, driveline park brake system
- Horn, single-note
- Rear Vision Camera, display integrated into Radio (Shipped loose in cab for upfitter installation.)
- Traction control

- Airbags, Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front and rear outboard seating positions; (Always use seat belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)
- Daytime Running Lamps, with automatic exterior lamp control
- OnStar, delete
- StabiliTrak, Electronic Stability Control System with Traction Control includes Electronic Trailer Sway Control and Hill Start Assist

Warranty

-3 Years/36,000 Miles. Rust-Through. 6 Years/100,000 Miles

Options

- 26,000 LB. GCWR (11,793 KG) (Requires 26k GCWR transmission (MWA, MWB, MIU, MIA, MH1, MGO, MIX, MF0, MA6 or MB6).) (R6G)
- 4G LTE WI-FI HOTSPOT CAPABLE (No longer available for ordering. Included and only available with (UE1) OnStar. Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. Terms and limitations apply. See onstar.com or dealer for details.) (VV4)
- ANTENNA EQUIPMENT includes additional antenna, cable and Groundplate Antenna, Cable and Groundplate will be shipped loose in the truck.) (Requires (UE1) OnStar and Chevrolet connected services capable or (U2K) SiriusXM Radio. (G7K)
- AXLE TO END OF FRAME, 75" (Requires (FRP) 235" wheelbase or (EQB) 219" wheelbase.) (F0I)
- ENGINE, DURAMAX 6.6L TURBO-DIESEL V8, B20-DIESEL COMPATIBLE 350 hp @ 2700 rpm, 700 lb.-ft. torque @ 1600 rpm (STD) (L5D)
- FRONT SUSPENSION, 7,000 LB. (3,175 KG) MULTI-LEAF, INCLUDES SHOCK ABSORBERS (STD) (FK6)
- HIGHWAY SERVICE TRANSMISSION, AUTOMATIC CLOSE-RATIO 6 SPD WITH DOUBLE OVERDRIVE, ALLISON, A1700HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, (STD) 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR, (C7R) 16,500 lb. GVWR, (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).) (MWA)
- KEY SYSTEM, 2 SPARE KEYS (5H1)
- ONSTAR AND CHEVROLET CONNECTED SERVICES CAPABLE Includes compass in instrument cluster. (Not available to order at this time. Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. Terms and limitations apply. See onstar.com or dealer for details.) (UE1)
- PAINT, SOLID (ZY1)
- REAR AXLE, 10,000 LB. (4,536 KG) DANA SPICER S14-110, SINGLE REDUCTION (FN1)
- REAR SUSPENSION, 11,000 LB. (4,990 KG) MULTI-LEAF, VARI-RATE (STD) (Not available with air suspension.) (GR3)
- SPARE TIRE DELETE (STD) (9L3)
- TIRES, FRONT 225/70R19.5G HIGHWAY BLACKWALL GOODYEAR Max Axle Load: 7,940 lb. (Requires (YAL) Tires, rear 225/70R19.5G highway blackwall Goodyear, Max Axle Load: 15,000 lb. or (YMF) Tires, rear 225/70R19.5G traction blackwall Goodyear, Max Axle Load: 15,000 lb.) (XDK)
- WHEELBASE, 235" (596.9 CM), 120" CA (Requires (F0I) 75" axle to end of frame.) (FRP)
- WORK TRUCK PREFERRED EQUIPMENT GROUP includes standard equipment (1WT)

- 4500 HD SERIES (Included and only available with (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR or (C7R) 16,500 lb. GVWR.) (R7M)
- ADDITIONAL FUEL, 5 GALLONS (8E4)
- AUDIO SYSTEM, 7" DIAGONAL COLOR TOUCH-SCREEN WITH CHEVROLET INFOTAINMENT AM/FM stereo with seek-and-scan and digital clock, includes Bluetooth streaming audio for music and select phones. (Not available to Order at this time. Not available with (TG5) Single slot CD/MP3 player.) (IOB)
- AXLE, LIMITED SLIP, DANA SPICER TRUETRAC, TORQUE PROPORTIONING LIMITED SLIP (G86)
- FRONT AXLE, 7,000 LB., DANA SPICER D800-N, "I"-BEAM, NON-DRIVING (Requires (FK6) 7,000 lb. (3,175 kg) front suspension.) (FTA)
- GVWR, 16,500 LB. (7484 KG) (STD) (Silverado 4500 HD 2WD Crew Cab models require one of the following combinations: (1) (FTA) 7k front axle and (FK6) 7k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension or (G40) 12K Rear air suspension. (2) (FTA) 7k front axle and (FK6) 7k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and one of the following rear suspensions: (GR4) 13.5k rear suspension, (FU7) 15.5k rear suspension, (GP1) 13.5K rear air suspension, (GP8) 15.5k rear air suspension, (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.) (C7R)
- JET BLACK, CLOTH SEAT TRIM includes manually adjustable driver lumbar (Not available with (APL) Passenger Seat Delete or (IO3) Audio System.) (H0U)
- LICENSE PLATE KIT, FRONT (will be shipped with trucks with ship-to states that require front license plate) (VK3)
- PAINT SCHEME, STYLE 1 (01U)
- POWER TAKE-OFF (PTO), NOT INSTALLED (PTX)
- REAR AXLE, 4.10 RATIO Max road speed: 79 MPH (066)
- SEATS, FRONT 40/20/40 SPLIT-BENCH, 3-PASSENGER driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar. (STD) (AE7)
- SUMMIT WHITE (GAZ)
- TIRES, REAR 225/70R19.5G HIGHWAY BLACKWALL GOODYEAR Max Axle Load: 15,000 lb. (Requires (XDK) Tires front 225/70R19.5G Highway blackwall Goodyear.) (YAL)
- WHEELS, 19.5" X 6.75", STEEL, BLACK PAINTED, 8-HOLES, HUB PILOTED (STD) (PWQ)