


<div>Year:<b>2023</b></div> <div>Make:<b>Chevrolet</b></div> <div>Model:<b>Silverado Chassis Cab</b></div> <div>VIN:<b>1HTKJPVM3PH430808</b></div>	<div>Engine:<b>Engine, Duramax 6.6L Turbo-Diesel V8</b></div> <div>Transmission:<b>Automatic</b></div> <div>Colors:<b>Summit White/Dark Ash Seats With Jet Black Interior Accents Cloth Seat Trim</b></div>
<div><div>CITY MPG /HIGHWAY MPG</div><div>NA</div><div><small>*MPG estimates on this website are EPA estimates; your actual mileage may vary. For used vehicles, MPG estimates are EPA estimates for the vehicle when it was new. The EPA periodically modifies its MPG calculation methodology; all MPG estimates are based on the methodology in effect when the vehicles were new (please see the Fuel Economy portion of the EPA's website for details, including a MPG recalculation tool).</small></div></div> <div></div>	<div>Price:<b>\$79,374</b></div> <div><small>*Prices do not include additional fees and costs of closing, including government fees and taxes, any finance charges, any dealer documentation fees, any emissions testing fees or other fees. All prices, specifications and availability subject to change without notice. Contact dealer for most current information</small></div>

Entertainment

- Audio system feature, 4-speaker system

-SiriusXM, delete
- Audio system, 4.2" diagonal color display AM/FM stereo with USB port and auxiliary jack (Requires (AE7) front 40/20/40 split-bench seat. Not available with (UE1) OnStar or (U2K) SiriusXM Radio.)

Exterior

- Antenna, fixed mast

-Bumper, front, Black

-Front fender extension, painted body color

-Grille guard screen, insect protection (mounted behind grille)

-Headlamps, halogen projector-beam

-Lamps, cargo area, cab mounted with switch on center switch bank

-Mirrors, outside high-visibility vertical camper-style, Black with manual folding and extension and lower convex spotter glass

-Tires, front 225/70R19.5G highway blackwall Pirelli Max Axle Load: 7,940 lb. (Standard on models built after July 17th, 2023) (Requires (YEY) Tires, rear 225/70R19.5G highway blackwall Pirelli, Max Axle Load: 15,000 lb. or (YEZ) Tires, rear 225/70R19.5G traction blackwall Pirelli, Max Axle Load: 15,000 lb.)

-Wheel, spare delete
- Assist steps

-Door handles, Black

-Glass, solar absorbing, tinted

-Grille, base, molded in color, Black

-Lamps, Smoked Amber roof marker

-Lamps, rear, stop/turn/backup (1-piece assembly) with license plate light

-Spare tire delete

-Tires, rear 225/70R19.5G highway blackwall Pirelli Max Axle Load: 15,000 lb. (Standard on models built after July 17th, 2023) (Requires (XEY) Tires front 225/70R19.5G Highway blackwall Pirelli.)

-Wheels, 19.5" x 6.75", steel, Black painted, 8-holes, hub piloted

Interior

- Air conditioning, single-zone

-Cruise control, steering wheel-mounted

-Driver Information Center, 3.5-inch diagonal monochromatic display, provides warning messages and basic vehicle information

-Instrumentation, 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure

-Mirror, inside rearview manual day/night

-Seat trim, Vinyl

-Speedometer, miles/kilometers

-Steering wheel, urethane

-Visors, driver and front passenger, vinyl
- Assist handle, front passenger and driver on A-pillars

-Door locks, power

-Floor covering, Graphite-colored rubberized-vinyl

-Interior trim, Jet Black/Dark Ash (Required and only available with (H2Q/H2R) Dark Ash seats with Jet Black interior accents.)

-Seat Belt, Black

-Seats, front 40/20/40 split-bench, 3-passenger driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar.

-Steering column, manual Tilt-Wheel

-Upfitter switch kit provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel

-Windows, manual driver and front passenger

Mechanical

- Alternator, 150 amps

-Axle lubricant, rear, synthetic oil EmGard FE -75W-90

-Axle, Open rear axle, non-locking rear

-Brakes, hydraulic, heavy duty Bosch/Meritor/Wabco system with 4-channel (ABS) (Includes (J69) driveline park brake.)

-Emissions, USA 50 State certified

-Exhaust brake

-Four wheel drive

-Front suspension, 7,500 lb. (3,402 kg) multi-leaf, includes shock absorbers

-Fuel, diesel B20

-Highway Service Transmission, Automatic close-ratio 6 SPD with double overdrive, Allison, A1700HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR, (C7R) 16,500 lb. GVWR, (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).)

-Neutral-at-Stop Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop, and remains in neutral until the service brake is released

-Rear axle, 4.30 ratio Max road speed: 75 MPH

-Steering, power (Bosch S2 8014 Plus)

-Trailerling provisions, trailerling wire harness only, trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.

-Wheelbase, 165" (419.1 cm), 84" CA (Requires (F0C) 49" axle to end of frame, (F0D) 63" axle to end of frame or (F0K) 91" axle to end of frame. Requires (PCJ) Vocational Specific Heavy Suspension Package, when ordering (FTA) 7,000 lb. Front axle/(FK6) 7,000 lb. Front suspension or (FTL) 8,000 lb. Front axle/(FSN) 8,000 lb. Front suspension or (FU7) 15,500 lb. rear suspension.)
- Axle lubricant, front, synthetic oil EmGard FE-75W-90

-Axle to End of Frame, 49" (Requires wheelbase (ED5) 201", (ED9) 165" or (ER2) 189". Not available with (G40), (GP1) or (GP8) rear air suspension.)

-Batteries, heavy-duty dual 1100 cold-cranking amps includes battery box mounted to left side under cab

-Capped Fuel Fill

-Engine, Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2700 rpm, 700 lb.-ft. torque @ 1600 rpm

-Exhaust system, rear exit

-Front axle, 7,500 lb., Dana Spicer 60-256, single-reduction, front driving

-Fuel tank, rear only, 40 gallon mounted between frame side rails and behind rear axle

-GVWR, 16,500 lb. (7484 kg) (Silverado 4500 HD 4WD models require one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension. (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension or (FU7) 15.5k rear suspension. (3) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (J27) 15.5k rear axle and one of the following rear suspensions: (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.)

-Incomplete vehicle

-Rear axle, 11,000 lb. (4,999 kg) Dana Spicer S14-110, single reduction

-Rear suspension, 11,000 lb. (4,990 kg) multi-leaf, vari-rate

-Trailer brake controller, integrated

-Transmission shift control calibration, fuel sense Performance

Safety

- Airbag deactivation switch, frontal passenger-side (Included and only available with (AY0) airbags.)

-Brake, parking, driveline park brake system

-Horn, single-note

-Rear Vision Camera, display integrated into Radio (Shipped loose in cab for upfitter installation.)

-Traction control
- Airbags, Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front outboard seating positions; Includes airbag deactivation switch for front outboard passenger airbag (Always use seat belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)

-Daytime Running Lamps, with automatic exterior lamp control

-OnStar, delete

-StabiliTrak, Electronic Stability Control System with Traction Control includes Electronic Trailer Sway Control and Hill Start Assist

Warranty

-3 Years/36,000 Miles. Rust-Through. 6 Years/100,000 Miles

## Options

-34,000 LB. GCWR (15,422 KG) (Requires 34k GCWR transmission (MBV/MBW/MBX/MBY/ME0/MHV/MIO/MJO). Requires (092) Rear axle, 4.30 ratio, and (HD1) 15k rear axle or (J27) 15.5k rear axle.) (R6W)

-6-SPEAKER AUDIO SYSTEM (Included and only available with (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment.) (UQ3)

-ADDITIONAL FUEL, 20 GALLONS (Not available with (NVK) front 25 gallon fuel tank.) (NXG)

-ASSIST STEPS, ALUMINUM (E0N)

-AUXILIARY HARNESS, 3' FOR HEADLAMPS AND TURN SIGNALS (Included with (VYU) Snow Plow Prep Package.) (UNL)

-BACKUP ALARM (Includes (SFW) SEO Calibration for backup alarm. Included with (YF2) Emergency Service Package.) (UZF)

-BATTERY, TOP POST THREADED, BATTERY JUMP START STUD (located on battery box) (Requires (7Y7) 1100 cold-cranking amps batteries or (7Y8) 1300 cold-cranking amps batteries.) (BTN)

-DARK ASH SEATS WITH JET BLACK INTERIOR ACCENTS, CLOTH SEAT TRIM includes manually adjustable driver lumbar (H2R)

-DPF, DIESEL PARTICULATE FILTER, MANUAL REGENERATION customer regeneration will not be allowed until the DPF load percentage has reached 100% full and a driver information center (DIC) message has been shown (Required with (YF2) Emergency Service Package.) (FPF)

-ENGINE, DURAMAX 6.6L TURBO-DIESEL V8, B20-DIESEL COMPATIBLE 350 hp @ 2700 rpm, 700 lb.-ft. torque @ 1600 rpm (STD) (L5D)

-FRONT AXLE, 7,500 LB., DANA SPICER 60-256, SINGLE-REDUCTION, FRONT DRIVING (FTB)

-FUEL TANK, FRONT AND REAR, 65 GALLON TOTAL (NSQ)

-GRILLE, CHROME (V22)

-HIGHWAY SERVICE TRANSMISSION AUTOMATIC CLOSE-RATIO 6 SPD WITH DOUBLE OVERDRIVE, ALLISON, A2750HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, includes park pawl. 26K GVW & 37K GCW Max., requires PTX, Available with GVWs greater than 19.5K (Requires (DD5) 21,000 lb. GVWR, (C5D) 22,500 lb. GVWR or (DB9) 23,000 lb. GVWR and (PTX) Power Take-Off (PTO), not installed, and (R6I) 30,000 lb. GCWR (13,607 kg) or (R6W) 34,000 lb. GCWR (15,422 kg).) (MBX)

-KEY SYSTEM, 2 SPARE KEYS (5H1)

-LICENSE PLATE KIT, FRONT (will be shipped with trucks with ship-to states that require front license plate) (VK3)

-ONSTAR AND CHEVROLET CONNECTED SERVICES CAPABLE Includes compass in instrument cluster. (Not available to order at this time. Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. Terms and limitations apply. See onstar.com or dealer for details.) (UE1)

-POWER OUTLET, 110-VOLT AC (KI4)

-PROVISION FOR CAB ROOF-MOUNTED LAMP/BEACON provides an overhead console mounted switch and electrical wiring tucked beneath the headliner for a body upfitter to connect a body-mounted warning or emergency lamp (Included with (VYU) Snow Plow Prep Package.) (TRW)

-REAR AXLE, 4.30 RATIO Max road speed: 75 MPH (092)

-RECOVERY HOOKS, FRONT, FRAME-MOUNTED, BLACK (Not available with (T3A) front bumper with 4" extension.) (V76)

-SEAT ADJUSTER, DRIVER 10-WAY POWER (Included and only available with (A52) front 40/20/40 split-bench seat.) (AG1)

-SHOCK ABSORBERS, REAR (Not available with (91B), (91C), (91D) or (91E) prep for LiquidSpring rear suspension (incomplete).) (G68)

-SKID PLATE, STEEL, FRAME-MOUNTED, PROTECTS THE TRANSFER CASE FROM THE GROUND (Not available with (7Y9) heavy-duty triple 2250 cold-cranking amp batteries.) (NZZ)

-SPARE TIRE DELETE (STD) (9L3)

-TIRES, FRONT 225/70R19.5 G TRACTION BLACKWALL CONTINENTAL Max Axle Load: 7,940 lb. (Requires (YHD) rear 225/70R19.5 G Traction Blackwall Continental tires.) (XHD)

-VOCATIONAL SPECIFIC HEAVY SUSPENSION PACKAGE Allows the selection of 7,000 lb., 8,000 lb., front axles and/or 15,500 lb. rear spring suspension on trucks that will be upfitted with the following vocational bodies: Utility/Service Bodies, Aerial Lift/Bucket bodies, Front Plow/Rear Spreader Applications, and Landscape Dump Bodies. For 141" or 165" WB trucks only. (Requires (ED9) 165" Wheelbase and (FU7) 15,500 lb. rear suspension.) (PCJ)

-WHEELS, 19.5" X 6.75", 4-ALUMINUM WHEELS, 8-HOLES, HUB PILOTED Dura-Bright finish is on the outside of the wheel (PWV)

-WORK TRUCK PREFERRED EQUIPMENT GROUP includes standard equipment (1WT)

-4G LTE WI-FI HOTSPOT CAPABLE (No longer available for ordering. Included and only available with (UE1) OnStar. Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. Terms and limitations apply. See onstar.com or dealer for details.) (VV4)

-6500 HD SERIES (Included and only available with (DD5) 21,000 lb. GVWR, (C5D) 22,500 lb. GVWR or (DB9) 23,000 lb. GVWR.) (R7P)

-ALTERNATOR, 220 AMPS (Included with (VYU) Snow Plow Prep Package.) (KW5)

-AUDIO SYSTEM, 7" DIAGONAL COLOR TOUCH-SCREEN WITH CHEVROLET INFOTAINMENT AM/FM stereo with seek-and-scan and digital clock, includes Bluetooth streaming audio for music and select phones. Includes (UQ3) 6-speaker audio system. (Not available to Order at this time. Not available with (TG5) Single slot CD/MP3 player.) (IOB)

-BACK-UP ALARM CALIBRATION This calibration will allow installation of an aftermarket back-up alarm by disabling rear perimeter lighting (SFW)

-BATTERIES, HEAVY-DUTY DUAL 1300 COLD-CRANKING AMPS includes battery box mounted to left side under cab (7Y8)

-BUMPER, FRONT CHROME (V46)

-DIFFERENTIAL, HEAVY-DUTY LOCKING REAR (Requires (J27) 15,500 lb. rear axle. Not available with (91B), (91C), (91D) or (91E) prep for LiquidSpring rear suspension. With (ED9) 165" Wheelbase, requires (PCJ) Vocational Specific Heavy Suspension Package or (9C2) 65 MPH road speed governor. Not available with (G40), (GP1) or (GP8) rear air suspensions when ordered with (ED9) 165" wheelbase. Not available with (G86) limited slip rear axle. Not available with (YF2) Emergency Service Package.) (G80)

-ENGINE BLOCK HEATER (K05)

-FOG LAMPS, FRONT, HALOGEN (T3U)

-FRONT STABILIZER BAR (F59)

-GRILLE GUARD SCREEN, STONE PROTECTION (mounted to bumper) (Not available with (T3A) front bumper with 4" extension.) (V23)

-GVWR, 22,500 LB. (10,206 KG) (Silverado 6500 HD 4WD models requires one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (FU7) 15.5k rear suspension. (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (J27) 15.5k rear axle and (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.) (C5D)

-HORN, DUAL-NOTE (U05)

-LABEL INFORMATION, CLEAN IDLE, DOOR LOCATION (VG7)

-MIRRORS, OUTSIDE HEATED POWER-ADJUSTABLE VERTICAL TRAILERING, UPPER GLASS, MANUAL-FOLDING AND EXTENDING, BLACK. Includes integrated turn signal indicators consisting of 51 square inch flat mirror surface positioned over a 24.5 square inch convex mirror surface with a common head and lower convex spotter glass (convex glass is not heated and not power adjustable) and addition of Auxiliary cargo lamp for backing up (helps to see trailer when backing up with a trailer) and amber auxiliary clearance lamp (Requires (A31) power windows.) (DPN)

-PAINT, SOLID (ZY1)

-POWER TAKE-OFF (PTO), NOT INSTALLED (PTX)

-REAR AXLE, 15,500 LB. (7,031 KG), DANA SPICER S16-130, SINGLE REDUCTION (Note: 15,500 lb. rear axle capacity can be reduced by rear tire capacity or rear suspension. Maximum axle capacity will not be higher than the rear tire or rear suspension capacity selected for vehicle.) (J27)

-REAR SUSPENSION, 15,500 LB. (7,031 KG) MULTI-LEAF, VARI-RATE (Requires (PCJ) Vocational Specific Heavy Suspension Package when ordered with (ED9) 165" Wheelbase.) (FU7)

-REMOTE KEYLESS ENTRY (AQQ)

-SEATS, FRONT 40/20/40 SPLIT-BENCH, CLOTH OR VINYL 3-PASSENGER. Includes driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Also includes manually adjustable driver lumbar and storage pockets. Includes (AG1) 10-way power seat.) (Not available to order at this time. Requires (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. (A52)

-SIRIUSXM RADIO enjoy a Platinum Plan trial subscription with over 150 channels including commercial-free music, plus sports, news and entertainment. Plus listening on the SiriusXM app, online and at home on compatible connected devices is included, so you'll hear the best SiriusXM has to offer, anywhere life takes you. Welcome to the world of SiriusXM. (Not available to Order at this time. Requires (UE1) OnStar and (IOB) 7" diagonal color touch-screen with Chevrolet Infotainment. IMPORTANT: The SiriusXM radio trial package is not provided on vehicles that are ordered for Fleet Daily Rental ("FDR") use. If you decide to continue service after your trial, the subscription plan you choose will automatically renew thereafter and you will be charged according to your chosen payment method at then-current rates. Fees and taxes apply. See the SiriusXM Customer Agreement at [www.siriusxm.com](http://www.siriusxm.com) for complete terms and how to cancel. All fees, content, features, and availability are subject to change.) (U2K)

-SNOW PLOW PREP PACKAGE includes (UNL) auxiliary harness for headlamps and turn signals, (KW5) 220-amp alternator, forward lamp wiring harness and (TRW) provision for cab roof mounted lamp/beacon (Note: (KW5) 220-amp alternator can be upgraded to (KHB) dual, 150 amps and 220 amps each alternators.) (VYU)

-SUMMIT WHITE (GAZ)

-TIRES, REAR 225/70R19.5 G TRACTION BLACKWALL CONTINENTAL Max Axle Load: 15,000 lb. (YHD)

-WHEELBASE, 165" (419.1 CM), 84" CA (STD) (Requires (F0C) 49" axle to end of frame, (F0D) 63" axle to end of frame or (F0K) 91" axle to end of frame. Requires (PCJ) Vocational Specific Heavy Suspension Package, when ordering (FTA) 7,000 lb. Front axle/(FK6) 7,000 lb. Front suspension or (FTL) 8,000 lb. Front axle/(FSN) 8,000 lb. Front suspension or (FU7) 15,500 lb. rear suspension.) (ED9)

-WINDOWS, POWER WITH DRIVER EXPRESS UP AND DOWN AND EXPRESS DOWN ON ALL OTHER WINDOWS (Requires (DPN) outside heated power-adjustable vertical trailering mirrors or (DGP) outside, black, heated power-adjustable, high-visibility vertical camper-style 102" wide load mirrors.) (A31)