


<div>Year:<b>2024</b></div> <div>Make:<b>Chevrolet</b></div> <div>Model:<b>Silverado Chassis Cab</b></div> <div>VIN:<b>1HTKJPVK5RH283103</b></div>	<div>Engine:<b>Engine, Duramax 6.6L Turbo-Diesel V8</b></div> <div>Transmission:<b>Automatic</b></div> <div>Colors:<b>Summit White/Jet Black Cloth Seat Trim</b></div>
<div><div>CITY MPG /HIGHWAY MPG</div><div>NA</div><div><small>*MPG estimates on this website are EPA estimates; your actual mileage may vary. For used vehicles, MPG estimates are EPA estimates for the vehicle when it was new. The EPA periodically modifies its MPG calculation methodology; all MPG estimates are based on the methodology in effect when the vehicles were new (please see the Fuel Economy portion of the EPA's website for details, including a MPG recalculation tool).</small></div></div> <div></div>	<div><div>Price:<b>\$82,110</b></div><div><small>*Prices do not include additional fees and costs of closing, including government fees and taxes, any finance charges, any dealer documentation fees, any emissions testing fees or other fees. All prices, specifications and availability subject to change without notice. Contact dealer for most current information</small></div></div>

Entertainment

- 6-speaker audio system

-SiriusXM, delete
- Audio system, 4.2" diagonal color display AM/FM stereo with USB port and auxiliary jack (Requires (AE7) front 40/20/40 split-bench seat. Not available with (UE1) OnStar or (U2K) SiriusXM Radio.)

Exterior

- Antenna, fixed mast

-Bumper, front, Black

-Front fender extension, painted body color

-Grille guard screen, insect protection (mounted behind grille)

-Headlamps, halogen projector-beam

-Lamps, cargo area, cab mounted with switch on center switch bank

-Mirrors, outside high-visibility vertical camper-style, Black with manual folding and extension and lower convex spotter glass

-Spare tire delete

-Tires, rear 225/70R19.5G highway blackwall Pirelli Max Axle Load: 15,000 lb. (Requires (XEY) Tires front 225/70R19.5G Highway blackwall Pirelli.)

-Wheels, 19.5" x 6.75", steel, Black painted, 8-holes, hub piloted
- Assist steps

-Door handles, Black

-Glass, solar absorbing, tinted

-Grille, base, molded in color, Black

-Lamps, Smoked Amber roof marker

-Lamps, rear, stop/turn/backup (1-piece assembly) with license plate light

-Paint, solid

-Tires, front 225/70R19.5G highway blackwall Pirelli Max Axle Load: 7,940 lb. (Requires (YEE) Tires, rear 225/70R19.5G highway blackwall Pirelli, Max Axle Load: 15,000 lb. or (YEZ) Tires, rear 225/70R19.5G traction blackwall Pirelli, Max Axle Load: 15,000 lb.)

-Wheel, spare delete

Interior

- Air conditioning, single-zone

-Cruise control, steering wheel-mounted

-Driver Information Center, 3.5-inch diagonal monochromatic display, provides warning messages and basic vehicle information (Included and only available with (IO3) Audio System with 4.2" diagonal color display or (IOR) Chevrolet Infotainment System with 7" diagonal color touch-screen.)

-Instrumentation, 6-gauge cluster featuring speedometer, fuel level, engine temperature, tachometer, voltage and oil pressure

-Mirror, inside rearview manual day/night

-Seat trim, Vinyl

-Seats, front 40/20/40 split-bench, 3-passenger driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Vinyl has fixed lumbar and cloth has manually adjustable driver lumbar.

-Steering column, manual Tilt-Wheel

-Upfitter switch kit provides up to 4-30 amp circuits to facilitate installation of aftermarket electrical accessories located on the instrument panel

-Windows, power with driver express up and down and express down on all other windows
- Assist handle, front passenger and driver on A-pillars

-Door locks, power

-Floor covering, Graphite-colored rubberized-vinyl

-Interior trim, Jet Black/Dark Ash (Required and only available with (H2Q/H2R) Dark Ash seats with Jet Black interior accents.)

-Seat Belt, Black

-Seat, rear 60/40 folding bench (folds up), 3-passenger (includes child seat top tether anchor)

-Speedometer, miles/kilometers

-Steering wheel, urethane

-Visors, driver and front passenger, vinyl

Mechanical

- Alternator, 150 amps

-Axle lubricant, rear, synthetic oil EmGard FE -75W-90

-Axle, Open rear axle, non-locking rear

-Brakes, hydraulic, heavy duty Bosch/Meritor/Wabco system with 4-channel (ABS) (Includes (J69) driveline park brake.)

-Emissions, USA 50 State certified

-Exhaust brake

-Four wheel drive

-Front suspension, 7,500 lb. (3,402 kg) multi-leaf, includes shock absorbers

-Fuel, diesel B20

-Highway Service Transmission, Automatic close-ratio 6 SPD with double overdrive, Allison, A1700HS ratios: 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 6TH Highway Series, 19.5K GVW & 26K GCW Max., requires PTX and park pawl. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR, (C7R) 16,500 lb. GVWR, (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR. Requires (R6G) 26,000 lb. GCWR (11,793 kg).)

-Neutral-at-Stop Automatic transmission shifts to neutral when the service brake is depressed while the vehicle is at a complete stop, and remains in neutral until the service brake is released

-Rear axle, 4.30 ratio Max road speed: 75 MPH

-Steering, power (Bosch S2 8014 Plus)

-Trailerling provisions, trailerling wire harness only, trailer combined (Stop/Tail/Turn) connection socket and harness mounted at rear of frame.

-Wheelbase, 175" (444.5 cm), 60" CA (Requires (F0C) 49" axle to end of frame. Not available with (N12) rear exit exhaust, or (NPK) right side exit exhaust ahead of rear wheels.)
- Axle lubricant, front, synthetic oil EmGard FE-75W-90

-Axle to End of Frame, 49" (Requires wheelbase (EM1) 199" or (FNV) 175". Not available with (G40), (GP1) or (GP8) rear air suspension.)

-Batteries, heavy-duty dual 1100 cold-cranking amps includes battery box mounted to left side under cab

-Capped Fuel Fill

-Engine, Duramax 6.6L Turbo-Diesel V8, B20-Diesel compatible 350 hp @ 2700 rpm, 750 lb.-ft. torque @ 1400 rpm

-Exhaust system, right side exit, behind rear wheels (Requires (FNV) 175" wheelbase.)

-Front axle, 7,500 lb., Dana Spicer 60-256, single-reduction, front driving

-Fuel tank, rear only, 40 gallon mounted between frame side rails and behind rear axle

-GVWR, 16,500 lb. (7484 kg) (Silverado 4500 HD 4WD models require one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension. (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension or (FUT) 15.5k rear suspension. (3) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (J27) 15.5k rear axle and one of the following rear suspensions: (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.)

-Incomplete vehicle

-Rear axle, 11,000 lb. (4,999 kg) Dana Spicer S14-110, single reduction

-Rear suspension, 11,000 lb. (4,990 kg) multi-leaf, vari-rate

-Trailer brake controller, integrated

-Transmission shift control calibration, fuel sense Performance

Safety

- Airbag deactivation switch, frontal passenger-side (Included and only available with (AY0) airbags.)

-Brake, parking, driveline park brake system

-Horn, single-note

-Rear Vision Camera, display integrated into Radio (Shipped loose in cab for upfitter installation.)

-Traction control
- Airbags, Single-stage frontal airbags for driver and front outboard passenger; Seat-mounted side-impact airbags for driver and front outboard passenger; Head-curtain airbags for front and rear outboard seating positions; (Always use seat belts and child restraints. Children are safer when properly secured in a rear seat in the appropriate child restraint. See the Owner's Manual for more information.)

-Daytime Running Lamps, with automatic exterior lamp control

-OnStar, delete

-StabiliTrak, Electronic Stability Control System with Traction Control includes Electronic Trailer Sway Control and Hill Start Assist

## Warranty

-5 Years/75,000 Miles

## Options

-34,000 LB. GCWR (15,422 KG) (Requires 34k GCWR transmission (MBV, MBW, MBX, MBY, ME0, MHV, MIO or MJ0). Requires (092) Rear axle, 4.30 ratio, and (HD1) 15k rear axle or (J27) 15.5k rear axle.) (R6W)

-ADDITIONAL FUEL, 20 GALLONS (Not available with (NVK) front 25 gallon fuel tank.) (NXG)

-ASSIST STEPS, ALUMINUM (E0N)

-BACK-UP ALARM CALIBRATION This calibration will allow installation of an aftermarket back-up alarm by disabling rear perimeter lighting (SFW)

-BATTERIES, HEAVY-DUTY DUAL 1300 COLD-CRANKING AMPS includes battery box mounted to left side under cab (7Y8)

-BUMPER, FRONT CHROME (V46)

-DIFFERENTIAL, HEAVY-DUTY LOCKING REAR (Requires (J27) 15,500 lb. rear axle. Not available with (91B), (91C), (91D) or (91E) prep for LiquidSpring rear suspension. With (ED9) 165" Wheelbase, requires (PCJ) Vocational Specific Heavy Suspension Package or (9C2) 65 MPH road speed governor. Not available with (G40), (GP1) or (GP8) rear air suspensions when ordered with (ED9) 165" wheelbase. Not available with (G86) limited slip rear axle. Not available with (YF2) Emergency Service Package.) (G80)

-DPF, DIESEL PARTICULATE FILTER, MANUAL REGENERATION customer regeneration will not be allowed until the DPF load percentage has reached 100% full and a driver information center (DIC) message has been shown (Required with (YF2) Emergency Service Package.) (FPF)

-ENGINE BLOCK HEATER (K05)

-FOG LAMPS, FRONT, HALOGEN (T3U)

-FRONT STABILIZER BAR (F59)

-GRILLE, CHROME (V22)

-HORN, DUAL-NOTE (U05)

-LICENSE PLATE KIT, FRONT (will be shipped with trucks with ship-to states that require front license plate) (VK3)

-MIRRORS, OUTSIDE HEATED POWER-ADJUSTABLE VERTICAL TRAILERING, UPPER GLASS, MANUAL-FOLDING AND EXTENDING, BLACK. Includes integrated turn signal indicators consisting of 51 square inch flat mirror surface positioned over a 24.5 square inch convex mirror surface with a common head and lower convex spotter glass (convex glass is not heated and not power adjustable) and addition of Auxiliary cargo lamp for backing up (helps to see trailer when backing up with a trailer) and amber auxiliary clearance lamp (DPN)

-POWER OUTLET, 110-VOLT AC (KI4)

-REAR AXLE, 15,500 LB. (7,031 KG), DANA SPICER S16-140, SINGLE REDUCTION (Note: 15,500 lb. rear axle capacity can be reduced by rear tire capacity or rear suspension. Maximum axle capacity will not be higher than the rear tire or rear suspension capacity selected for vehicle.) (J27)

-REAR SUSPENSION, 15,500 LB. (7,031 KG) MULTI-LEAF, VARI-RATE (FU7)

-RUGGED DUTY SERVICE TRANSMISSION, AUTOMATIC CLOSE-RATIO 6 SPD WITH DOUBLE OVERDRIVE, ALLISON, A1750RDS ratios 3.10 1ST, 1.80 2ND, 1.40 3RD, 1.00 4TH, 0.70 5TH, 0.61 Rugged Duty Series, 19.5K GVW & 37.5K GCW Max., requires PTO and park pawl, On/Off Highway. Available with GVWs less than or equal to 19.5K (Requires (C7Y) 14,001 lb. GVWR, (C5B) 15,000 lb. GVWR, (C7P) 16,000 lb. GVWR, (C7R) 16,500 lb. GVWR, (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR. Requires (R6I) 30,000 lb. GCWR (13,607 kg) or (R6W) 34,000 lb. GCWR (15,422 kg).) (MIO)

-SEATS, FRONT 40/20/40 SPLIT-BENCH, CLOTH OR VINYL 3-PASSENGER. Includes driver and front passenger recline with outboard head restraints and center fold-down armrest with storage. Also includes manually adjustable driver lumbar and storage pockets. Includes (AG1) 10-way power seat.) (Requires (IO5) Chevrolet Infotainment Audio system with 8" diagonal color touch-screen or (IOR) Chevrolet Infotainment System with 7" diagonal color touch-screen. (A52)

-SINGLE-SLOT CD/MP3 PLAYER (Included with (IO5) Chevrolet Infotainment Audio system with 8" diagonal color touch-screen. Not available with (IOR) Chevrolet Infotainment System with 7" diagonal color touch-screen.) (TG5)

-STEERING WHEEL, LEATHER-WRAPPED WITH AUDIO AND CRUISE CONTROLS (Included and only available with (IO5) Chevrolet Infotainment Audio system with 8" diagonal color touch-screen.) (NP5)

-TIRE, SPARE 225/70R19.5G TRACTION BLACKWALL GOODYEAR Includes (V33) Rim Wrench and handle only tool kit.) (Requires (YMF) 225/70R19.5G Goodyear traction blackwall rear tires. (ZMF)

-TIRES, REAR 225/70R19.5G TRACTION BLACKWALL GOODYEAR Max Axle Load: 15,000 lb. (Requires (XDK) Tires front 225/70R19.5G Highway blackwall Goodyear or (XMF) Tires front 225/70R19.5G Traction blackwall Goodyear.) (YMF)

-WHEEL, 19.5" X 6.75", SPARE, ALUMINUM, 8-HOLES temporary mounted on frame. Dura-Bright finish is on the outside of the wheel. (Required and only available with (PWV) 19.5" x 6.75", aluminum, 8-holes, hub piloted wheels or (PWG) 19.5" x 6.75", 6-aluminum, 8-holes, hub piloted wheels when a spare tire is ordered.) (PWZ)

-WHEELS, 19.5" X 6.75", 4-ALUMINUM WHEELS, 8-HOLES, HUB PILOTED Dura-Bright finish is on the outside of the wheel (PWV)

-5500 HD SERIES (Included and only available with (GZX) 17,500 lb. GVWR, (GZJ) 18,000 lb. GVWR or (GZG) 19,500 lb. GVWR.) (R7N)

-ALTERNATORS, DUAL, 150 AMPS AND 220 AMPS EACH (Included with (YF2) Emergency Service Package.) (KHB)

-AUDIO SYSTEM, CHEVROLET INFOTAINMENT SYSTEM WITH 8" DIAGONAL COLOR TOUCH-SCREEN AM/FM stereo with seek-and-scan and digital clock, includes Bluetooth handsfree calling and streaming audio with select phones; wired phone projection via select 3rd party apps; USB ports; auxiliary jack; voice-activated technology for radio and phone; and Shop with the ability to browse, select and install apps to your vehicle. Apps include Pandora, iHeartRadio, The Weather Channel and more. (Includes (TG5) Single-slot CD/MP3 player, (UDD) 4.2" diagonal Driver Information Center, (NP5) Leather-wrapped steering wheel, and (UK3) Steering Wheel Audio Controls. Requires (A52) Front 40/20/40 split-bench seats.) (IO5)

-BACKUP ALARM (Includes (SFW) SEO Calibration for backup alarm. Included with (YF2) Emergency Service Package.) (UZF)

-BATTERY, TOP POST THREADED, BATTERY JUMP START STUD (located on battery box) (Requires (7Y7) 1100 cold-cranking amps batteries or (7Y8) 1300 cold-cranking amps batteries.) (BTN)

-DEFOGGER, REAR-WINDOW ELECTRIC (C49)

-DOOR HANDLES, OUTSIDE, CHROME (E20)

-DRIVER INFORMATION CENTER, 4.2-INCH DIAGONAL COLOR DISPLAY, INCLUDES DRIVER PERSONALIZATION, WARNING MESSAGES AND VEHICLE INFORMATION (Included and only available with (IO5) Chevrolet Infotainment Audio system with 8" diagonal color touch-screen.) (UDD)

-ENGINE, DURAMAX 6.6L TURBO-DIESEL V8, B20-DIESEL COMPATIBLE 350 hp @ 2700 rpm, 750 lb.-ft. torque @ 1400 rpm (STD) (L5D)

-FRONT AXLE, 7,500 LB., DANA SPICER 60-256, SINGLE-REDUCTION, FRONT DRIVING (FTB)

-FUEL TANK, FRONT AND REAR, 65 GALLON TOTAL (Not available with (NPJ) left side exit exhaust system ahead of rear wheels when ordered with (FNV) 175" wheelbase.) (NSQ)

-GVWR, 17,500 LB. (7938 KG) (Silverado 5500 HD 4WD models require one of the following combinations: (1) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (FN1) 10k rear axle or (GL4) 11k rear axle and (GR3) 11k rear suspension. (2) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD2) 13.5k rear axle and (GR4) 13.5k rear suspension. (3) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (HD1) 15k rear axle or (J27) 15.5k rear axle and (GR4) 13.5k rear suspension or (FU7) 15.5k rear suspension. (4) (FTB) 7.5k front axle and (FTV) 7.5k front suspension and (J27) 15.5k rear axle and one of the following rear suspensions: (91B) 13.5k LiquidSpring prep single volume rear suspension, (91C) 13.5k LiquidSpring prep stacked volume rear suspension, (91D) 15.5k LiquidSpring prep single volume rear suspension or (91E) 15.5k LiquidSpring prep stacked volume rear suspension.) (GZX)

-JET BLACK, CLOTH SEAT TRIM includes manually adjustable driver lumbar (Not available with (APL) Passenger Seat Delete or (IO3) Audio System.) (HOU)

-MIRROR CAPS, CHROME (Requires (DPN) heated power-adjustable vertical trailering mirrors.) (DP9)

-PAINT SCHEME, STYLE 1 (01U)

-POWER TAKE OFF, ENGINE CONTROL PROVISIONS Access is available on left-hand and right-hand side (PTO)

-REAR AXLE, 4.30 RATIO Max road speed: 75 MPH (092)

-REMOTE KEYLESS ENTRY (AQQ)

-SEAT ADJUSTER, DRIVER 10-WAY POWER (Included and only available with (A52) front 40/20/40 split-bench seat.) (AG1)

-SHOCK ABSORBERS, REAR (Not available with (91B), (91C), (91D) or (91E) prep for LiquidSpring rear suspension (incomplete).) (G68)

-STEERING WHEEL AUDIO CONTROLS (Included and only available with (IO5) Chevrolet Infotainment Audio system with 8" diagonal color touch-screen.) (UK3)

-SUMMIT WHITE (GAZ)

-TIRES, FRONT 225/70R19.5G TRACTION BLACKWALL GOODYEAR Max Axle Load: 7,940 lb. (Requires (YMF) rear 225/70R19.5G traction blackwall Goodyear tires.) (XMF)

-TOOL KIT, RIM WRENCH AND HANDLE ONLY (Included with (ZBK), (ZMF), (ZEY), (ZEZ), (ZBT), (ZBU), (ZBV) and (ZBW) spare tires.) (V33)

-WHEELBASE, 175" (444.5 CM), 60" CA (STD) (Requires (F0C) 49" axle to end of frame. Not available with (N12) rear exit exhaust, or (NPK) right side exit exhaust ahead of rear wheels.) (FNV)

-WORK TRUCK PREFERRED EQUIPMENT GROUP includes standard equipment (1WT)